Fittings / LED Street Lights

# Alto 75W LED IP66 Street Light with Nema Socket - 4000K



The Alto LED Street Light offers flexibility, it is suitable for use in many locations, including rural towns, car parks and access roads. The Alto is available in a variety of wattages for a variety of applications, and is a robust weatherproof construction meeting an IP66 protection rating.

- 150 lm/W.
- Genuine Replacement for 70W Son or Metal Halide.
- Ideal for car parks and pedestrian walkways.
- Reduced light pollution.
- Precision lens system directs light only where it is needed, reducing overspill.
- Aerodynamic design for reduced windage.
- 60mm side or post top entry.
- 3 Pin Nema socket with blanking plug as standard.

## Technical Specification

| | 30W | 50W | 75W | 100W | 150W | |
|---|---|---|---|---|---|---|
| Length (mm) | SE 523 / PTE 409 | SE 523 / PTE 409 | SE 629 / PTE 515 | SE 629 / PTE 515 | SE 724 / PTE 610 | SE Side Entry<br>PTE Post Top Entry |
| Width (mm) | SE 146 / PTE 146 | SE 146 / PTE 146 | SE 174 / PTE 174 | SE 174 / PTE 174 | SE 194 / PTE 194 | |
| Height (mm) | SE 134 / PTE 248 | SE 134 / PTE 248 | SE 135 / PTE 249 | SE 135 / PTE 249 | SE 137 / PTE 251 | |




| | |
|---|---|
| **Product Code** | 11702 |

## Reference

| | |
|---|---|
| **Guarantee** | 7 Years |
| **EAN** | 5013588117027 |
| **Commodity Code** | 9405423990 |
| **Country of Origin** | CN |
| **UNSPSC Code** | 39111608 |

**E:** sales@belllighting.co.uk
**T:** 01924 893380



This document is uncontrolled if printed, all information is subject to change. Generated on 10/5/2024 5:20:53 PM

## Technical Specification

| | |
|---|---|
| **Volts (V)** | 220/240 |
| **Watts (W)** | 75 |
| **Colour Temp (K)** | 4000 |
| **Dimmable?** | No |
| **Lumens (lm)** | 11250 |
| **Life Hours** | 50000 |
| **CRI (ra)** | 85 |
| **Switching Cycles** | 80000 |
| **Frequency (Hz)** | 50/60 |
| **LED Drive Current** | 107mA |
| **Energy Consumption (kWh/1000h)** | 75 |
| **IP Rating** | IP66 |
| **Impact Protection** | IK8 |

## Dimensions

| | |
|---|---|
| **Height (mm)** | 135 |
| **Width (mm)** | 174 |
| **Length (mm)** | 629 |

## Packaging Information

| | |
|---|---|
| **Single Carton Height (mm)** | 135 |
| **Single Carton Width (mm)** | 185 |
| **Single Carton Depth (mm)** | 510 |
| **Single Carton Weight (kg)** | 3.3 |
| **Individual Volume** | 0.01274 |
| **Outer Box Qty** | 1 |



This document is uncontrolled if printed, all information is subject to change. Generated on 10/5/2024 5:20:53 PM